GIOVANNI BARBIERI ARTISAN TILE AND STONE DESIGNER


SOLID MARBLE MOSAIC

FOR



SOLID MARBLE MOSAIC





LIGHT TRAVERTINE

SOLID MOSAIC

SOLID MOSAIC WAS CREATED BY GIOVANNI BARBIERI AND GIVES
THE NATURAL STONE WALL A NEW AESTHETIC APPEARANCE
BETWEEN A TRADITIONAL, NATURALLY SPLIT SURFACE
AND A CONTEMPORARY, DEEPLY THOUGHT-OUT CONCEPT.

A SOLID MARBLE STRIP OF 2" X 2" CROSS-SECTION IS APPLIED TO THE WALL IN DIFFERENT WAYS: ONE SHOWS THE RAW CUT SURFACE AND ANOTHER THE NATURALLY SPLIT SURFACE.

EFFECTIVELY, THIS MOSAIC IS 3/8 (1CM) THICK.

WHEN INSTALLED, IT LOOKS LIKE A SOLID STRIP OF MARBLE THAT IS
BROKEN ON THE SURFACE AND SHOWS ITS NATURAL SPLIT SURFACE,
GIVING A NEW DECORATIVE RESULT.
SOLID SINGLE PIECES FOR CORNER COVERS IN "L" SECTION ARE ALSO AVAILABLE.

MOSAIC SHEET ON NET 3/8 THICKNESS






6x30x1 Cm loose strips or interlock panels on net Engineered Marble and Gypsum








LIGHT TRAVERTINE / THE NEW SPA AT 5 STARS HOTEL BRISTOL WARSAW, SINCE 1902,








LIGHT TRAVERTINE / THE NEW SPA AT 5 STARS HOTEL BRISTOL WARSAW, SINCE 1902










LIGHT TRAVERTINE / CORNER COVER SPECIAL PIECES.

ENGINEERED MARBLE

6 COLOUR OPTIONS






WHITE LIMESTONE LIGHT TRAVERTINE






JASMINE

BROWN





IRON GREY

DARK GREY

AVAILABLE IN 6 ENGINEERED MARBLE AND PLASTER MONOCHROME WHITE SUITABLE FOR 100% DRY PLACES ONLY, COULD BE PAINTED ONCE INSTALLED

ENGINEERED MARBLE & GYPSUM THREE DIMENSIONAL TILES

THE ENGINEERED MARBLE CARVED TILES ARE PRODUCED, THROUGH A LABORATORY TESTED PROCESS, BY RECYCLING MARBLE DUST FROM THE PRODUCTION WASTE REFUSE THUS FAITHFULLY REPRODUCING THE TRAVERTINE AND NATURAL STONE.

SUITABLE FOR ANY INSTALLATION/CLIMATE CONDITION EVEN WHERE NATURAL STONE IS NOT SUGGESTED. NO MAINTENANCE. NOT ABSORBENT. LABORATORY TESTED UNALTERABLE COLOUR FROM UV RADIANT. THIS PROCESS ALSO HELP TO OBTAIN 3D DRAWINGS THAT ARE IMPOSSIBLE TO BE PRODUCED IN NATURAL OR JUST WITH "LUNAR" PRICE.

TO HELP INTERIORS INSTALLATION REDUCE COST ONLY, THE ENGINEERED MARBLE PRODUCTS ARE ALSO AVAILABLE IN GYPSUM AT MUCH MORE REASONABLE COST BUT SUITABLE IN 100% DRY PLACE ONLY WHERE IS POSSIBLE TO PAINT ON SITE AT INSTALLATION COMPLETED.

ENGINEERED MARBLE LABORATORY TEST CERTIFICATES BY TILE COUNCIL OF NORTH AMERICA AND SETTING INSTRUCTIONS ARE BELOW AVAILABLE ON NEXT PAGES



PRODUCT TESTING SERVICE

100 Clemson Research Blvd.

Anderson, SC 29625 Tel (864) 646-TILE Fax (864) 646-2821

TCNA TEST REPORT NUMBER:

TCNA-585-14

PAGE: 1 **OF** 2

TEST REQUESTED BY:

Petrastone SRL

TEST METHOD: ASTM C97: "Absorption and Bulk Specific Gravity of Dimension Stone"

Informal Test Method Description: These test methods cover the tests for determining the absorption and bulk specific gravity of all types of dimension stone, except slate. These test methods are useful in indicating the differences in absorption between the various dimension stones. See ASTM C97 for all method details and information.

TEST SUBJECT MATERIAL: Identified by client as: "Petrastone"

Approximate Size as Received: 3"x3"x3"

TEST DATE: 10/13/2014 - 10/15/2014

TEST PROCEDURE:

- Sample prep: None
- The specimens were dried in an oven for 48 hours before a dry weight was recorded for each specimen.
- The specimens were then submerged in water for an additional 48 hours before measuring the saturated and suspended weights.
- The weight percent absorption and the density were then calculated based on the weight measurements made.

TEST RESULTS:

	% Water Absorption	Density (lb/ft ³)
Specimen 1	0.08	114.2
Specimen 2	0.07	109.5
Specimen 3	0.07	118.6
Specimen 4	0.06	119.1
Specimen 5	0.07	117.9
Average:	0.07	115.9

COMMENTS: None

10/31/2014

Laboratory Manager

Testing Services: testing@tileusa.com Literature Orders: literature@tileusa.com Web Site: www.tileusa.com This report is confidential and has been prepared for the exclusive use of the client. It is not an endorsement, approval, certification, or

criticism of any product by TCNA. This report shall not be published in any form without prior written consent from TCNA

ENGINEERED MARBLE LABORATORY TEST CERTIFICATES



PRODUCT TESTING SERVICE

100 Clemson Research Blvd.

TEST SUBJECT MATERIAL:

Anderson, SC 29625 Tel (864) 646-TILE Fax (864) 646-2821

TCNA TEST REPORT NUMBER:

TCNA-585-14

PAGE: 2 OF 2

TEST REQUESTED BY:

Petrastone SRL

Identified by client as: "Petrastone"

ASTM C97: "Absorption and Bulk Specific Gravity of Dimension Stone"

ASTM SPECIFICATIONS*:

ASTM standard	Stone Type	Specification
ASTM C503	Marble – Calcite	Maximum 0.20% Absorption; Minimum 162 lb/ft ³ Density
ASTM C503	Marble – Dolomite	Maximum 0.20% Absorption; Minimum 175 lb/ft ³ Density
ASTM C1527	Travertine (Interior or	Maximum 2.5% Absorption; Minimum 144 lb/ft ³ Density
	Exterior)	
ASTM C568	Limestone (Low Density)	Maximum 12.0% Absorption; Minimum 110 lb/ft ³ Density
ASTM C568	Limestone (Medium Density)	Maximum 7.5% Absorption; Minimum 135 lb/ft ³ Density
ASTM C568	Limestone (High Density)	Maximum 3.0% Absorption; Minimum 160 lb/ft ³ Density
ASTM C615	Granite	Maximum 0.40% Absorption; Minimum 160 lb/ft³ Density

^{*}For more detailed information, refer to ASTM C503 Specification for Marble Dimension Stone, ASTM C1527 Specification for Travertine Dimension Stone, ASTM C568 Specification for Limestone Dimension Stone, and ASTM C615 Specification for Granite Dimension Stone

10/31/2014

Laboratory Manager

Literature Orders: literature@tileusa.com Web Site: www.tileusa.com Testing Services: testing@tileusa.com

This report is confidential and has been prepared for the exclusive use of the client. It is not an endorsement, approval, certification, or criticism of any product by TCNA. This report shall not be published in any form without prior written consent from TCNA



PRODUCT TESTING SERVICE

100 Clemson Research Blvd.

Anderson, SC 29625 Tel (864) 646-TILE Fax (864) 646-2821

TCNA TEST REPORT NUMBER:

TCNA-585-14

PAGE: 1 **OF** 2

TEST REQUESTED BY: Petrastone SRL

ASTM C372: "Standard Test Method for Linear Thermal Expansion of TEST METHOD:

Porcelain Enamel and Glaze Frits and Fired Ceramic Whiteware Products by

the Dilatometer Method"

This test method covers the determination of the linear thermal expansion of ceramic whiteware products by the thermal dilatometer method. This test method consists of determining the linear thermal expansion of ceramic and glass tile using a dilatometer between the temperatures of 25°C (77°F) and 100°C (212°F).

TEST SUBJECT MATERIAL: Identified by client as: "Petrastone"

Approximate Size as Received: 6"x6"

TEST DATE: 10/8/2014

TEST PROCEDURE:

- Sample Prep: Sample was cut to approximately 25 mm x 8 mm x 8 mm
- The linear thermal expansion was determined using a Netzsch 402C Dilatometer located at the Bishop Materials Laboratory, Clemson University.
- The temperature range was 25°C 100°C.

TEST RESULTS:

Temperature	Linear Thermal
Range (°C)	Expansion
	(per °C)
25°C to 50°C	19.6084 x 10 ⁻⁶
25°C to 80°C	25.5609 x 10 ⁻⁶
25°C to 100°C	29.7947 x 10 ⁻⁶

10/31/2014

Laboratory Manager

Literature Orders: literature@tileusa.com Web Site: www.tileusa.com

Testing Services: testing@tileusa.com This report is confidential and has been prepared for the exclusive use of the client. It is not an endorsement, approval, certification, or criticism of any product by TCNA. This report shall not be published in any form without prior written consent from TCNA



PRODUCT TESTING SERVICE

TCNA TEST REPORT NUMBER: TCNA-585-14

PAGE: 2 **OF** 2

ASTM C372: "Standard Test Method for Linear Thermal Expansion of Porcelain Enamel and Glaze Frits and **TEST METHOD:**

Fired Ceramic Whiteware Products by the Dilatometer Method"

TEST SUBJECT MATERIAL:

Identified by client as: "Petrastone"




Figure 1: Dilatometer Analysis

10/31/2014 Laboratory Manager

This report is confidential and has been prepared for the exclusive use of the client. It is not an endorsement, approval, certification, or criticism of any product by TCNA. shall not be published in any form without prior written consent from TCNA



PRODUCT TESTING SERVICE

100 Clemson Research Blvd.

Anderson, SC 29625 Tel (864) 646-TILE Fax (864) 646-2821

PAGE: 1 **OF** 1 TCNA TEST REPORT NUMBER: TCNA-585-14

TEST REQUESTED BY: Petrastone SRL

ASTM C482-02 (2009): "Standard Test Method for Bond Strength of **TEST METHOD:**

Ceramic Tile to Portland Cement"

Informal Test Method Description: This test method covers the determination of the ability of glazed ceramic wall tile, ceramic mosaic tile, quarry tile, and pavers to be bonded to portland cement paste. This test method includes both face-mounted and back-mounted tile. This test method consists of bonding tile under controlled conditions to a pure portland cement paste bond coat, supported by a cement mortar bed.

This summary is provided for the reader's convenience and is not a complete description of the method. See ASTM C482 for all method details and information.

Identified by client as: "Petrastone" **TEST SUBJECT MATERIAL:**

Approximate Size as Received: 4"x4"

TEST DATE: 10/9/2014 - 10/16/2014

TEST PROCEDURE:

- Sample prep: None
- The ASTM C482 test method was modified per the client's request*. The client requested to test the bond strength of tile to a concrete substrate using an epoxy.
- Four (4) bond strength specimens were created by securing the tile specimens to $1-\frac{1}{2} \times 7-\frac{7}{8} \times 15-\frac{3}{4}$ -inch concrete blocks with Laticrete Latapoxy 310.
- The specimens were cured for seven (7) days before testing. The specimens were loaded in shear at a rate of 200 psi/min.

TEST RESULTS:

	Bond Strength (psi)	Mode of Failure
Specimen 1	691 psi	Failure within stone
Specimen 2	1150 psi	Partial block failure; partial stone failure
Specimen 3	758 psi	Block failure
Specimen 4	707 psi	Block failure
Average	827 psi	

*COMMENTS: The ASTM C482 test method was modified per the client's request. The method states to bond the tile to Portland cement mortar block using a Portland cement paste. The modifications are described above.

> 10/31/2014 Makhy Dung

Katelyn Simpson

Laboratory Manager

Testing Services: testing@tileusa.com Literature Orders: literature@tileusa.com Web Site: www.tileusa.com

This report is confidential and has been prepared for the exclusive use of the client. It is not an endorsement, approval, certification, or criticism of any product by TCNA. This report shall not be published in any form without prior written consent from TCNA



PRODUCT TESTING SERVICE

100 Clemson Research Blvd. TCNA TEST REPORT NUMBER:

Anderson, SC 29625 Tel (864) 646-TILE Fax (864) 646-2821

PAGE: 1 **OF** 1

TEST REQUESTED BY:

Petrastone SRL

TCNA-585-14

TEST METHOD: ASTM C666: "Standard Test Method for Resistance of Concrete to Rapid Freezing and Thawing", Procedure A: Rapid Freezing and Thawing in Water

Informal Test Method Description: This test method covers the determination of the resistance of concrete (or other materials) to rapidly repeated cycles of freezing and thawing in water. The test method consists of alternately lowering the temperature of the specimens from 40 to 0°F (4 to -18°C) and raising it from 0 to 40°F (-18 to 4°C) in not less than 2 nor more than 4 hours (not less than 25% of the time is used for thawing). The number of freeze-thaw cycles is recorded and typically after 300 cycles the test load is visually examined for damage, checked for percent weight loss, percent length change, and a durability factor is calculated based on the relative dynamic modulus of elasticity.

This summary is provided for the reader's convenience and is not a complete description of the method. See ASTM C666 for all method details and information.

TEST SUBJECT MATERIAL: Identified by client as: "Petrastone"

Approximate Size as Received: 3" x 3"

TEST DATE: 10/13/2014 - 10/27/2014

TEST PROCEDURE:

• Sample Prep: None

- All testing was performed by The Bishop Material Laboratory of Clemson University.
- The specimens were subjected to fifty (50) cycles of freezing the specimens in water from 40 to 0°F and then thawing the specimens in water from 0 to 40°F per the client's request
- Since only 50 cycles were performed, the relative dynamic modulus of elasticity was not measured. The percent weight change and any visual observations are reported below.

TEST RESULTS:

		Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5	Average
Weight	Initial Weight (grams)	143.4 g	142.3 g	132.5 g	151.0 g	146.3 g	
Change after 300	Final Weight (grams)	143.3 g	142.3 g	132.3 g	150.9 g	146.2 g	
Cycles	Weight Change, %	0.1%	0.0%	0.2%	0.1%	0.1%	0.1%
Visual	Observations	No visual deterioration					

COMMENTS: None

Kathyding 10/31/2014

Katelyn Simpson

Laboratory Manager

Testing Services: testing@tileusa.com Literature Orders: literature@tileusa.com Web Site: www.tileusa.com

This report is confidential and has been prepared for the exclusive use of the client. It is not an endorsement, approval, certification, or criticism of any product by TCNA. This report shall not be published in any form without prior written consent from TCNA

Research Triangle Park Laboratories Inc, 7201 ACC Blvd., Raleigh, NC 27617

California 01350/ASTM D5116 Small Chamber Tests for Volatile Organic Compound Emissions From Products

Project ID: 14-177


Client: Tile Council of North America Sample Receipt Date: Oct 17, 2014

Test Start Date: Oct 30, 2014 Products:

Petrastone Engineered Stone

Modeled Star	ndard Clas	sroom Con	centration	ı, mg/m3
24 hr	48 hr	96 hrl	LOQ	

24	hr 48	3 hr 96	hr LC	Q
0.0	0.0	0.0	0.0	01



Standard Classroom Model Parameters:

Room Dimensions: 40 ft length x 24 ft wide x 8.5 ft ht

Room Volume: 231 m³

Ventilation Rate: 0.90 air changes per hour


Net Floor Surface: 89.2 m²

Chamber and Sample Conditions:

Chamber Volume: 50 Liters

Temperature: 20-25 C; Relative Humidity: 45-55 % Air Exchange Rate: 1 per hour (0.833L/min = 50 liters)

Sample Surface Area: 0.0232 m² Sample Loading Factor: 0.5 m²/m³







TEST REPORT

Report No.: F0338.01-121-24 **Test Date**: September 1, 2015

Rendered to:

PETRA STONE S.R.L. Ariccia, Italy

PRODUCT TYPE: Petra Stone SERIES/MODEL: Engineered Stone

TEST METHOD: ASTM E 84-15a, Standard Test Method for Surface Burning Characteristics of Building Materials

Summary of ASTM E 84 Test Results		
Flame Spread Index Smoke Developed Index		
5	105	

This report contains in its entirety:

Cover Page: 1 page
Report Body: 6 pages
Graphs: 1 page
Photographs: 1 page

Reference must be made to Architectural Testing, Inc. Report No. F0338.01-121-24 for complete test specimen descriptions.





1.0 Report Issued To: Petra Stone S.r.l.

Via Nettunense km13 00040 Ariccia, Rome

Italy

2.0 Test laboratory: Architectural Testing, Inc.

130 Derry Court

York, Pennsylvania 17406-8405

717-764-7700

3.0 Introduction:

The Steiner Tunnel test apparatus is used to evaluate the surface burning characteristics and smoke development of building materials. The tunnel is considered to be under calibrated conditions when the flame front reaches the end of the tunnel within 5 minutes and 30 seconds (plus or minus 15 seconds) during a red oak test. An initial preheat of the tunnel is performed and the test specimen is installed when the tunnel temperature drops to $105^{\circ}F$. When the test is initiated, the 88 KW dual burner and 240 feet per minute air current creates a flame that extends 4.5 feet down the tunnel. The flame progression is tracked from this point to the exhaust end of the tunnel which is 19.5 feet downstream. An observer simultaneously notes any test specimen anomalies such as melting, dripping, sagging, delamination, fall-out, etc. The smoke that is generated during the test is measured by a photometer. The flame spread and smoke developed data are automatically logged and graphed versus time by a data acquisition and computer system. The Flame Spread Index (FSI) and the Smoke Developed Index (SDI) are based on an area under the curve calculation and the red oak flooring calibration data.

4.0 Project Summary:

4.1 Product Type: Petra Stone

4.2 Series/Model: Engineered Stone

- 4.3 Compliance Statement: Results obtained are tested values and were secured by using the designated test method(s). The specimen(s) were tested to evaluate the flame spread and smoke developed properties. A summary of the results is listed in the Test Results section and the complete graphical test data is included in Appendix A of this report.
- **4.4 Test Date**: 9/1/2015
- 4.5 Test Location: Architectural Testing, Inc., test facility in York, Pennsylvania.
- **4.6 Test Sample Source**: The test specimen was provided by the client. Representative samples of the test specimen will be retained by Architectural Testing for a minimum of four years from the test completion date.

130 Derry Court York, PA 17406	www.archtest.com
-----------------------------------	------------------

www.archtest.com • www.intertek.com/building

p. 717.764.7700f. 717.764.4129





Test Report No.: F0338.01-121-24 Report Date: 9/10/2015 Test Record Retention End Date: 9/10/2019 Page 2 of 6

4.0 Project Summary: (Continued)

4.7 List of Official Observers:

Name Company

Mark Freeborn Architectural Testing, Inc.
Robert George Architectural Testing, Inc.

5.0 Test Method(s), Practices and/or Classifications:

ASTM E 84-15a, Standard Test Method for Surface Burning Characteristics of Building Materials

6.0 Test Specimen Description:

Date Tested:	9/1/2015
Manufacturer*:	Petra Stone S.r.l.
Product Type:	Petra Stone
Series/Model:	Engineered Stone
Composition*:	Marble Dust & Resin
Conditioning Time:	72+ hr.
Specimen Size:	12 in. wide x 39 in. long
Thickness:	1/2 in.
Specimen Sections:	16
Total Weight:	16.23 lbs.
Color:	Light Grey
Side to Flame:	Upper
Support Used*:	1/4 in. diameter steel rods spaced 24 inches
Mounting Method:	E84-15a (X1.1.1.3)
Substrate Used*:	N/A
Cement Board:	The fiber cement board was placed on top of the sample.

^{*}From the client's material description and/or instructions

Note: Specimens were conditioned as per the requirements of Section 6.4 of ASTM E84-15a Standard Test Method for Surface Burning Characteristics of Building Materials

130 Derry Court York, PA 17406	www.archtest.com • www.intertek.com/building	p. 717.764.7700 f. 717.764.4129
-----------------------------------	--	------------------------------------





Page 3 of 6

7.0 Test Results: The test results are tabulated as follows:

Test Results			
Flame Spread Index (FSI): 5			
Smoke Developed Index (SDI):	105		
Test Operator:	Mark Freeborn		
Red Oak Calibration (% * Min):	94.8		

Test Data		
FSI (unrounded):	7.0	
SDI (unrounded):	102.9	
FS * Time Area (Ft * Min):	13.7	
Smoke Area (% * Min):	97.5	
Fuel Area (°F * Min):	4429.4	

Observations		
Ignition Time:	03:43 (Min:Sec)	
Max Flame Front Advance:	4.7 Feet	
Time to Max Flame Front:	09:43 (Min:Sec)	
Max Temp At Exposed T/C:	551.1°F	
Time To Max Temp:	09:58 (Min:Sec)	
Dripping Observed:	No	
Flaming On Floor Observed:	09:27 (Min:Sec)	
After Flame Top Observed:	10:02 (Min:Sec)	
After Flame Floor Observed:	10:03 (Min:Sec)	
Sagging Observed:	No	
Delamination Observed:	No	
Shrinkage Observed:	No	
Fallout Observed:	04:09 (Min:Sec)	
Cracking Observed:	00:14 (Min:Sec)	
Observations After the Test:	None	

Reference Appendix A for graphs.

130 Derry Court York, PA 17406 www.archtest.com • www.intertek.com/building p. 717 f. 717

p. 717.764.7700f. 717.764.4129





Test Report No.: F0338.01-121-24 Report Date: 9/10/2015 Test Record Retention End Date: 9/10/2019

Page 4 of 6

7.0 Test Results: (Continued)

In Accordance with ASTM E 84-15a the use of supporting materials on the underside of the test specimen has the ability to lower the flame spread index from those which might be obtained if the specimen could be tested without such support. These test results do not necessarily relate to indices obtained by testing materials without such support (E84-15a, 1.3).

This standard is used to measure and describe the response of materials, products, or assemblies to heat and flame under controlled conditions, but does not by itself incorporate all factors required for fire-hazard or fire-risk assessment of the materials, products, or assemblies under actual fire condition s (E84-15a, 1.7).

This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the sole responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use (E84-15a, 1.8).

8.0 Codes and Regulations:

The 2009 International Building Code® (Chapter 8 Interior Finishes, Section 803 Wall and Ceiling Finishes) and NFPA 5000, (Chapter 10 Interior Wall or Ceiling Finish Testing and Classification) classify materials based on their Flame Spread and Smoke Developed indices. The classification criteria are listed below:

Classification	Flame Spread Index	Smoke Developed Index
A	0-25	0-450
В	26-75	0-450
C	76-200	0-450

130 Derry Court York, PA 17406 www.archtest.com • www.intertek.com/building p. 717.764.7700 f. 717.764.4129





Page 5 of 6

The service life of this report will expire on the stated Test Record Retention End Date, at which time such materials as drawings, data sheets, samples of test specimens, copies of this report, and any other pertinent project documentation, shall be discarded without notice.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory. It is the exclusive property of the client so named herein and relates only to the specimen(s) tested. This report may not be reproduced, except in full, without the written approval of Architectural Testing, Inc.

For ARCHITECTURAL TESTING, Inc.

Mark Freeborn

Matthew Freeborn Manager – Fire Testing

MGF:ddr

Attachments (pages): This report is complete only when all attachments listed are included.

Appendix-A: Graphs (1) Appendix-B: Photographs (1)

Technician – Fire Testing

This report produced from controlled document template ATI 00537, revised 12/04/14.

130 Derry Court York, PA 17406

www.archtest.com • www.intertek.com/building

p. 717.764.7700 f. 717.764.4129





Test Report No.: F0338.01-121-24 Report Date: 9/10/2015 Test Record Retention End Date: 9/10/2019 Page 6 of 6

Revision Log

Rev. #	Date	Page(s)	Revision(s)
0	9/10/2015	N/A	Original Report Issue

130 Derry Court York, PA 17406 www.archtest.com • www.intertek.com/building p. 717.764.7700 f. 717.764.4129





Appendix A

Graphs


130 Derry Court York, PA 17406 www.archtest.com • www.intertek.com/building


p. 717.764.7700f. 717.764.4129






Test Report No.: F0338.01-121-24 Report Date: 9/10/2015 Test Record Retention End Date: 9/10/2019







130 Derry Court York, PA 17406

www.archtest.com • www.intertek.com/building

p. 717.764.7700f. 717.764.4129





Appendix B
Photographs

130 Derry Court York, PA 17406

www.archtest.com • www.intertek.com/building

p. 717.764.7700 f. 717.764.4129





Test Report No.: F0338.01-121-24 Report Date: 9/10/2015 Test Record Retention End Date: 9/10/2019



Photo No. 1 Specimen Mounted (Pre-test)



Photo No. 2 Specimen Mounted (Post-test)

130 Derry Court York, PA 17406

www.archtest.com • www.intertek.com/building

p. 717.764.7700f. 717.764.4129

Engineered Marble 3D Design by Giovanni Barbieri SETTING INSTRUCTIONS by: Decorstone SRL

SETTING INSTRUCTIONS

Under standard installation conditions the following instructions must be CAREFULLY observed:

ADHESIVES

Recommended adhesives for: 3D SERIES- Giovanni Barbieri Design Series

INTERIOR AND EXTERIOR APPLICATIONS:

KERAKOLL EXTREME (A+B), MAPEI KERALASTIC T or BENFER BENFERJOLLY.

Use:

During preliminary installation pieces must be selected simultaneously from different boxes.

The adhesive should be applied both on the piece and installation surface (double-spreading technique).

Application should begin from below and the corner profiles applying forward/reverse motion achieving a uniform setting, any excess adhesive should be removed using a dry spatula or sponge.

PRECAUTIONS

Decor Stone products are intended to be used for coverings application only. Use of non-specific adhesives may cause improper installation.

Application temperature should range between 5°C and 25°C, above 25°C the setting layer should be dampened with enough water and pieces installed on the moist surface.

Do not install on irregular or painted surfaces.

Do not install on degraded\humid plaster coverings.

Do not install on light mortar or lime, any dust should be removed.

Installation surfaces subject to high temperatures must be properly isolated.

Expansion joints must be applied every 10 sq.m. for exterior installations,

25 sq.m. for interior installations and every 8 metres in lenght for long and
narrow surfaces. Structural, split and perimeter joints must be observed.

Use of specific adhesives and setting methods indicated on our official
documents refers to normal interior/exterior surface application not
subject to particular conditions out of the standard building code


Non-standard applications must be discussed before installation in order to receive the most suitable setting solution.

DECOR STONE SHALL NOT BE DEEMED RESPONSIBLE FOR ANY ISSUE WHICH MAY ARISE FROM SUCH INSTALLATIONS IF NOT CONTACTED BEFOREHAND.

NOTE

Decor Stone shall not be liable to any installation issue should the mentioned setting instructions not be followed.

AWARDS





BESTOTYEAR INTERIOR DESIGN HONOREE 2011







BEST OF YEAR 2013









ARCHITECTURAL R E C O R D









OVERALL WINNER with "The Fine Lines Terrazzo" Collection.

BIOGRAPHY

Giovanni started his career at the age of 14 by operating in the marble sector as a go-getter.

When he was 16 years old he was capable of completing independently floorings within his older brother's business.

In 1984, at the age of 18, Giovanni contributed 50% of the investment entering into business partnership with his brother by establishing F.LLI Barbieri.

In those days the company had already begun to produce tumbled marbles for its own realizations.

At the age of 22, Giovanni began attending school courses in interior design between 1989 and 1997. The best results were achieved in the building site projects - projects in which he worked together with the architects who taught the classes.

These collaborations reinforced a period of strong progression: Giovanni was the only project developer and supplier of marble tiles that came exclusively from the Family Stone company and personally supervised the installation.

The emphasis was placed on the production process and the design of new products; first for the local market, then all the way to the United States, mainly thanks to the excellent understanding of design in research and development and the longstanding excellent collaboration with Nancy Epstein.

Many patents have been developed towards the End of '90s such as "MARMO ANTICO LUCIDO"; "FRAMENTI BORDER"; "TIMEWORN MARBLE" and more after.

Giovanni participated in some Contemporary Art Competitions receiving a special mention in Torino in 2003 with Roberto Lanaro, an European Renewed Metal Artist-Sculptor.

In 2008 "AMBRA COLLECTION" received an American Architecture award and was exposed at "Triennale Design Museum" in Milan for more than one year.

In 2010 Giovanni started his successful collaboration with Sara Baldwin developing irreproducible Timeworn Mosaics still one of its best seller after 10 years, as well as Ambra.

Giovanni Barbieri has been a source of inspiration for many renowned brands resulting in the successful reproduction of his Inventions and Techniques; AMBRA is a simply example reproduced by many.

In 2013 the first Engineered 3D Marble Tiles Collections Exciton/ Hive was awarded at Best-Of-Year INTERIOR DESIGN. This Collection is produced by recycling marble dust from production waste for high performance installation where natural stone is not suggested.

In 2013 the Memento Porcelain Tile Collection is Best-of-Year INTERIOR DESIGN Award-winner with Vallelunga Ceramica.

In 2014 Giovanni is the Winner of the London Surface Design Award with "CLAS" on Belgian project.

2015 is the year of Murano Collection, Award Winner at Best-Of-Year INTERIOR DESIGN, NYC.

In 2016, the world's first true 3D porcelain tile collection "TRILOGY", winner of BoY INTERIOR DESIGN, will be presented in the USA and New York City Design Award in May 2017 at the MoMa in NYC.

2017 marks the launch of new shading flat 3D wall tiles: "Collection RR".

In 2018 a new chapter begins with new Antiqued handmade Black terracotta tiles in an "easy-care" version: the "Minimal Rustic Collection".

2018-19-20 is the initial success of the SQUAR Collection, between tile collection and Art performance, triple awarded in the USA also at the BoY Awards, and by ARCHITECTURAL RECORD USA Magazine also with the handmade ceramic tile collection "KLE".

The year 2020 is not yet over and the Terrazzo Collection "The Fine Lines" just nominated Overall Winner at latest SBID (The Society of British International Interior Design) product design Awards in London.

Dear esteemed customer,

we would like to THANK YOU for your support for Giovanni Barbieri Design and Products,

We are facing a very strange and delicate time and we try to manage the future in the most appropriate way.

Now, as never before, we firmly believe in the potential of the latest, absolutely unique tile collections developed by Giovanni Barbieri, whose combination with the Design Service of the project is suitable for every single use. Only the same inventor of the collection can offer the best and most accurate interpretation, more like an artistic performance than a tile collection.

We supply pre-assembled panels that offer the highest quality of Italian artisan realizations allowing quick installation at the final site, with cost effective solutions and unparalleled aesthetic results of custom-made art.

This helps all A&D studios and dealers a lot, avoiding any misunderstanding by intermediaries, with direct negotiation in the highest professional behaviuour, reducing cost and improving the final quality result.

In trust of our 40 years of experience and reputation, we have created a link on the home page where you can quickly upload your project drawings and fill out a form to explain all details of your tile project design request:

https://www.giovannibarbieri.com/project_request we are now able to guarantee to send back our design proposal and full cost including door to door shipping service in 1 up to 2 working days.

We hope that this new combination of products and services will help create a new, easy, fast and highly professional way to realize your projects in an artistic way.

Sincerely Giovanni Barbieri

WWW.GIOVANNIBARBIERI.COM INFO@GIOVANNIBARBIERI.COM SCHIAVON - VICENZA - ITALY



IT IS FORBIDDEN TO REPRODUCE ANY PART OF THIS CATALOGUE