

Step outside. Floor innovation

via Circonvallazione Sacchetti 148 48015 Cervia (RA) tel. +39 0544 1766513 info@zocchetto.com

zocchetto.com

Material Description	Outdoor paving system made of plastic, wood, and stone granulate, stone granulate, brass and copper
Component Nature	Tile in HIPS plastic, PEFC-certified wood, and stone granulate, metal
Module Dimensions	Width: 11 cm - Length: 11 cm - Height: 5.5 cm
Total Weight (minimum ÷ maximum)	28 kg/sq.m
Total Thickness	5,5 cm
Drive-Over Capability	Courtyard areas, pedestrian urban spaces with service vehicle access, residential parking lots.
Cleanability	Cleaning with neutral pH soap and a brush. After treatment, rinse thoroughly with water
Drainage Capacity	I/m² 31,5 I/min 29,1 (Cp) 100% permeability coefficient
Slip Resistance	Leather on dry surface: 0.99 / Rubber on wet surface: 0.78 (According to Italian Ministerial Decree of June 14, 1989, No. 236)
Slip resistance for pedestrian surfaces	R13 (according to DIN EN 16165:2023-02 standard)
CAM	Meets the CAM (Minimum Environmental Criteria) sustainability requirements







Commercial



Outdoor



Patented



Suitable for Vehicle Transit



Class 4 Impregnated



Shockproof



Relocatable



Flexible



1 mq = 28 kg

≣co-friendly

Durable



100% recyclable





Recycled plastic

PEFC wood